



Hampton GCi60 biomass pellet insert shown with ceramic log set.

FEATURES

- Ability to burn a variety of biomass pellet fuels: high grade to low grade wood, corn, wheat and barley
- Durable cast iron exterior provides beautiful radiant heat
- Fluted cast iron liner
- Low maintenance burner with agitator rod in the burn pot
- Reduced cleaning intervals compared to other pellet stoves
- Quick start automatic (400 watts) ignitor with air pump
- 300 CFM convection variable speed blower
- Standard wall thermostat
- Concealed, easy-to-use controls with Tri-mode operating system (Manual – Hi/Lo – Auto/Off)
- Advanced air wash system for cleaner glass
- Large concealed ash drawer

OPTIONS

- Ceramic one piece log set
- Oversize filler panel

SPECIFICATIONS	GCi60
BTU input (on high)*	55,000
BTU input (on low)*	10,000
Efficiency (EPA LHV)	64.5%
Emissions (grams/hour)	1.82 g/hr
Fuel capacity (hopper size)	60 lbs
Burn time (typical)	up to 36 hrs.
Room size / Area heated**	up to 2,500 sq. ft.
Weight	500 lbs
Max. power usage (ignitor on)	504 Watts
Operating power usage	200 Watts
Vent size	4"
Viewing area	232 sq. in.
MINIMUM FIREPLACE OPENING	
Width (front)	27"
Height	23"
Depth	16"

* Figure will vary with individual conditions and fuel quality.
** Figure will vary with floor plan, house layout / heat loss of the house and quality of pellets used.





Hampton GC60 biomass pellet stove shown with ceramic log set.

FEATURES

- Ability to burn a variety of biomass pellet fuels: high grade to low grade wood, corn, wheat and barley
- Durable cast iron exterior provides beautiful radiant heat
- Fluted cast iron liner
- Low maintenance burner with agitator rod in the burn pot
- Reduced cleaning intervals compared to other pellet stoves
- Quick start automatic (400 watts) ignitor with air pump
- 300 CFM convection variable speed blower
- Standard wall thermostat
- Concealed, easy-to-use controls with Tri-mode operating system (Manual – Hi/Lo – Auto/Off)
- Advanced air wash system for cleaner glass
- Mobile home approved
- Large concealed ash drawer

OPTIONS

- Ceramic one piece log set

SPECIFICATIONS	GC60
BTU input (on high)*	55,000
BTU input (on low)*	10,000
Efficiency (EPA LHV)	64.5%
Emissions (grams/hour)	1.82 g/hr
Fuel capacity (hopper size)	60 lbs
Burn time (typical)	up to 36 hrs.
Room size / Area heated**	up to 2,500 sq. ft.
Weight	504 lbs
Max. power usage (ignitor on)	504 Watts
Operating power usage	200 Watts
Vent size	4"
Viewing area	232 sq. in.

* Figure will vary with individual conditions and fuel quality.

** Figure will vary with floor plan, house layout / heat loss of the house and quality of pellets used.





Greenfire GFi55 pellet insert with antique copper door overlay and ceramic log set.

FEATURES

- Large arched bay door
- Black door overlay
- Steel fluted liner panels
- Hidden door handle
- Decorative black grilles
- Heavy-duty heat exchanger
- Large concealed ash drawer
- Large 55 lb hopper with easy access lid and recessed handle
- Adjustable hopper height from 22.75" to 19.5"
- 160 CFM convection variable speed blower
- Concealed, easy-to-use controls with Tri-mode operating system (Manual – Hi/Lo – Auto/Off)
- Quick start ignitor (300 Watts)

OPTIONS

- Antique copper door overlay
- Brushed nickel door overlay
- Ceramic one piece log set
- Regular or oversize faceplate

SPECIFICATIONS	GFi55
BTU input (on high)*	45,000
BTU input (on low)*	12,000
Efficiency (EPA LHV)	74.5%
Emissions (grams/hour)	0.89 g/hr
Fuel capacity (hopper size)	55 lbs
Burn time (typical)	up to 36 hrs.
Room size / Area heated**	up to 2,000 sq. ft.
Max. power usage (ignitor on)	520 Watts
Operating power usage	200 Watts
Vent size	3"
Viewing area	161 sq. in.
MINIMUM FIREPLACE OPENING	
Width (front)	26"
Height	19-1/2" - 22-3/4"
Depth	15"

* Figure will vary with individual conditions and fuel quality.
 ** Figure will vary with floor plan, house layout / heat loss of the house and quality of pellets used.





Greenfire GF55 pellet stove shown with brushed nickel door overlay and ceramic log set.

FEATURES

- Large arched bay door
- Black door overlay
- Steel fluted liner panels
- Hidden door handle
- Decorative black grilles
- Heavy-duty heat exchanger
- Large full pedestal ash drawer
- Large 55 lb hopper with easy access lid and recessed handle
- 160 CFM convection variable speed blower
- Concealed, easy-to-use controls with Tri-mode operating system (Manual – Hi/Lo – Auto/Off)
- Quick start ignitor (300 Watts)
- Mobile home approved

OPTIONS

- Antique copper door overlay
- Brushed nickel door overlay
- Ceramic one piece log set

SPECIFICATIONS	GF55
BTU input (on high)*	45,000
BTU input (on low)*	12,000
Efficiency (EPA LHV)	74.5%
Emissions (grams/hour)	0.89 g/hr
Fuel capacity (hopper size)	55 lbs
Burn time (typical)	up to 36 hrs.
Room size / Area heated**	up to 2,000 sq. ft.
Max. power usage (ignitor on)	520 Watts
Operating power usage	200 Watts
Vent size	3"
Viewing area	161 sq. in.

* Figure will vary with individual conditions and fuel quality.
** Figure will vary with floor plan, house layout / heat loss of the house and quality of pellets used.





Greenfire GF40 shown with hearth pad.

FEATURES

- Ability to burn a variety of pellet fuels - high grade to low grade wood pellets
- Low maintenance burner and easy to clean burn pot
- Concealed, easy-to-use controls with Tri-mode operating system (Manual - Hi/Lo - Auto/Off)
- Large multi-tube heat exchanger
- 130 CFM convection variable speed blower
- Mobile home approved
- Quick start automatic (400 watt) ignitor
- Large concealed ash drawer
- Standard matching hearth pad

SPECIFICATIONS	GF40
BTU input (on high)*	30,000
BTU input (on low)*	8,000
Efficiency (EPA LHV)	70.7%
Emissions (grams/hour)	0.48 g/hr
Fuel capacity (hopper size)	up to 67 lbs
Burn time (typical)	up to 36 hrs.
Room size / Area heated**	up to 1,200 sq. ft.
Weight	230 lbs
Max. power usage (ignitor on)	475 Watts
Operating power usage	215 Watts
Vent size	3"
Viewing area	124 sq. in.

* Figure will vary with individual conditions and fuel quality.
 ** Figure will vary with floor plan, house layout / heat loss of the house and quality of pellets used.

