



LR13E shown with Vignette faceplate in Black and Old Town Red interior panels.

STANDARD FEATURES

- Natural gas
- Safety screen with ceramic safety glass
- High definition 7 piece log set with ceramic burner and glowing ember bed
- Proflame II GTMF remote control system
- Variable speed blower for max heat distribution
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs and colors
- Interior panels in Old Town Red, Rustic Brown or Volcanic Black
- Reflective black enamel interior panels
- Small, regular, arched, oversized and custom backing plates
- Hearth trim kit and mantel deflector
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	20,500	19,000
Turn down to (BTU)	14,000	15,500
Efficiency (steady state)	73.12%	74.59%
EnerGuide Rating (Canada only)	66.25%	66.70%

DIMENSIONS	
Viewing Area	28-1/2"
Width	21-5/8"
Height	19-1/2"
Depth	14-1/2"



HRI3E shown with Vignette faceplate in Black, Black Crystals with Volcanic Stones and Black Reflective Enamel panels.

STANDARD FEATURES

- Natural gas
- Safety screen with ceramic safety glass
- Regency Horizon contemporary linear fire bed with black steel interior panels
- Proflame II GTMF remote control system
- Variable speed blower for max heat distribution
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs and colors
- Firebeads and crystals in various colors
- Driftwood log set, Volcanic Stones, Spa Stones or River Pebbles
- Reflective black enamel interior panels
- Small, regular, arched, oversized and custom backing plates
- Hearth trim kit and mantel deflector
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	19,500	19,000
Turn down to (BTU)	14,000	15,500
Efficiency (steady state)	71.73%	72.87%
EnerGuide Rating (Canada only)	64.36%	66.24%

DIMENSIONS	
Viewing Area	28-1/2"
Width	21-5/8"
Height	19-1/2"
Depth	14-1/2"



LRI4E shown with regular backing plate, Vignette faceplate in Black, Door Inlay in Black and Rustic Brown Brick Panels.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- High definition log set
- Ceramic burner with glowing ember bed
- Electronic ignition with SureFire™ switch
- Proflame I GTMF remote control
- Variable speed blower for max heat distribution
- 6-tube heat exchanger for max efficiencies
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs & colors
- Faceplate spacer for shallow fireplace installations
- Interior panels in Old Town Red, Rustic Brown or Volcanic Black
- Reflective Black Enamel Interior Panels
- Small, regular, arched, oversized and custom backing plates
- Mantel deflector for reduced clearances
- Hearth trim kits for raised hearth installations
- Wall thermostat
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	31,000	31,000
Turn down to (BTU)	22,000	26,000
Efficiency (steady state)	71.45%	73.01%
EnerGuide Rating (Canada only)	70.27%	69.36%

DIMENSIONS	
Width (front)	30"
Width (rear)	22"
Height	20"
Depth (without spacer)	18"
Depth (with spacer)	15-3/4"



HRI4E shown with 4-sided regular backing plate, Vignette faceplate in Platinum with Black Crystals and optional Driftwood log set.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Ceramic burner with glowing ember bed
- Electronic ignition with SureFire™ switch
- Proflame I GTMF remote control
- Variable speed blower for max heat distribution
- 6-tube heat exchanger for max efficiencies
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs & colors
- Faceplate spacer for shallow fireplace installations
- Crystals or firebeads in various colors
- Volcanic Stones, Spa Stones, or accent River Pebbles
- Driftwood log set
- Reflective black enamel interior panels
- Small, regular, arched, oversized and custom backing plates
- Mantel deflector for reduced clearances
- Hearth trim kits for raised hearth installations
- Wall thermostat
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	31,000	31,000
Turn down to (BTU)	22,000	26,000
Efficiency (steady state)	71.45%	73.01%
EnerGuide Rating (Canada only)	70.27%	69.36%

DIMENSIONS	
Width (front)	30"
Width (rear)	22"
Height	20"
Depth (without spacer)	18"
Depth (with spacer)	15-3/4"



LRI6E shown with regular backing plate, Vignette faceplate in black, craftsman inlay in tuscan sunset.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- High definition log set
- Ceramic burner with glowing ember bed
- Black steel interior panels
- Electronic ignition with SureFire™ switch
- Proflame I GTMF remote control
- Variable speed blower for max heat distribution
- 6-tube heat exchanger for max efficiencies
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs & colors
- Faceplate spacer for shallow fireplace installations
- Interior panels in Old Town Red, Rustic Brown or Volcanic Black
- Reflective black enamel interior panels
- Small, regular, arched, oversized and custom backing plates
- Mantel deflector for reduced clearances
- Hearth trim kits for raised hearth installations
- Wall thermostat
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	38,000	38,000
Turn down to (BTU)	25,000	30,000
Efficiency (steady state)	73.01%	73.01%
EnerGuide Rating (Canada only)	70.37%	70.37%

DIMENSIONS	
Width (front)	34"
Width (rear)	25"
Height	24"
Depth (without spacer)	19-1/2"
Depth (with spacer)	16-3/4"



HRI6E shown with regular backing plate, Vignette faceplate in Black Chrome with Black Crystals and optional Driftwood log set.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Ceramic burner with glowing ember bed
- Black steel interior panels
- Electronic ignition with SureFire™ switch
- Proflame I GTMF remote control
- Variable speed blower for max heat distribution
- 6-tube heat exchanger for max efficiencies
- 30° angled flue for versatile installation
- Direct vent
- Limited lifetime warranty

OPTIONS

- Vignette faceplates in various designs and colors
- Vignette inlays in various designs & colors
- Faceplate spacer for shallow fireplace installations
- Crystals or firebeads in various colors
- Volcanic Stones, Spa Stones, or accent River Pebbles
- Driftwood log set
- Reflective black enamel interior panels
- Small, regular, arched, oversized and custom backing plates
- Mantel deflector for reduced clearances
- Hearth trim kits for raised hearth installations
- Wall thermostat
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	38,000	38,000
Turn down to (BTU)	25,000	30,000
Efficiency (steady state)	73.01%	73.01%
EnerGuide Rating (Canada only)	70.37%	70.37%

DIMENSIONS	
Width (front)	34"
Width (rear)	25"
Height	24"
Depth (without spacer)	19-1/2"
Depth (with spacer)	16-3/4"



E33 shown with Low Profile faceplate and Brick panels.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Proflame GTM remote control
- Log set with glowing embers
- Flame height adjustment control
- Variable speed blower
- 30° angled flue for versatile installations
- Standing pilot system
- Direct spark ignition
- Limited lifetime warranty

OPTIONS

- Faceplates in low profile or Vignette design
- Vignette door inlay in various colors
- Custom backing plate
- Brick panels
- Wall thermostat
- Installation spacer
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	38,000	35,500
Turn down to (BTU)	20,000	19,000
Efficiency (steady state)	70.14%	70.73%
EnerGuide Rating (Canada only)	60.70%	61.49%

DIMENSIONS	
Width (front)	32-1/4"
Width (rear)	25"
Height	24-3/16"
Depth (without spacer)	18"
Depth (with spacer)	16-3/4"



U31 shown with Low Profile faceplate and Brick panels.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Proflame GT remote control
- Log set with glowing embers
- Flame height adjustment control
- Variable speed blower
- Standing pilot system
- Direct spark ignition
- B vent
- Installation spacer
- Limited lifetime warranty

OPTIONS

- Low profile faceplates
- Custom backing plate
- Contour faceplate
- Hearth trim kit
- Black louvers
- Brick panels
- Basic or programmable wall thermostat
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	30,000	27,500
Turn down to (BTU)	14,500	13,700
Efficiency (steady state)	58.45%	59.29%
EnerGuide Rating (Canada only)	51.42%	47.41%

DIMENSIONS	
Width (front)	26-1/2"
Width (rear)	22-1/2"
Height	21"
Depth (without spacer)	--
Depth (with spacer)	15"



E21 shown with Low Profile faceplate and Brick panels.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Proflame GTM remote control
- Log set with glowing embers
- Flame height adjustment control
- Variable speed blower
- Standing pilot system
- Direct spark ignition
- B vent
- Installation spacer
- Limited lifetime warranty

OPTIONS

- Low profile faceplates
- Custom backing plate
- Brick panels
- Basic or programmable wall thermostat
- 4" to 3" flue collar
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	23,500	22,000
Turn down to (BTU)	11,750	11,250
Efficiency (steady state)	61.63%	64.65%
EnerGuide Rating (Canada only)	49.29%	52.88%

DIMENSIONS	
Width (front)	26-1/2"
Width (rear)	18"
Height	17-3/4"
Depth (without spacer)	13-1/8"
Depth (with spacer)	14-3/8"



L234 shown with Low Profile faceplate and Brick panels.

STANDARD FEATURES

- Natural gas
- Safety screen
- Ceramic safety glass
- Proflame GTM remote control
- Log set with glowing embers
- 30° angled flue for versatile installation
- Variable speed blower
- Installation spacer
- Flame height adjustment control
- Standing pilot system
- Direct spark ignition
- Direct vent
- Limited lifetime warranty

OPTIONS

- Low profile faceplate
- Custom backing plate
- Adjustable hearth riser
- Brick panels
- Basic or programmable thermostat
- 3" to 2" air intake reducer
- Regency flex liners
- Propane conversion kit

SPECIFICATIONS

SPECIFICATIONS	NATURAL GAS	PROPANE
Input (BTU)	23,500	21,500
Turn down to (BTU)	12,500	11,000
Efficiency (steady state)	73.94%	74.67%
EnerGuide Rating (Canada only)	63.34%	64.73%

DIMENSIONS	
Width (front)	25"
Width (rear)	16"
Height	17"
Depth (without spacer)	14"
Depth (with spacer)	14-3/8"